

Description

Accurate seed placement and adjustable metering. Unlike broadcast seeders, the Bobcat® seeder places the seed with the proper spacing and at precisely the right depth for better germination. It also eliminates broadcasting seed into unwanted areas. With a production rate of more than two acres per hour, the seeder is efficient and cost-effective.

Dimensions

Description	Item number	Overall length (A) (mm)	Overall width (B) (mm)	Overall height (C) (mm)
Seeder 182 cm, 3-Point Mounting, Non-CE	7167712	-	1820.0	-

Weights

Description	Item number	Operating weight (kg)	Shipping weight (kg)
Seeder 182 cm, 3-Point Mounting, Non-CE	7167712	590.0	590.0

Main features

- 182 cm seeding width.
- Variable seeding rate.
- Three-point mount standard.

Applications

- Agriculture
- Landscaping

Loader Compatibility

Description	Item number	Compatible with loader	Functional requirements
Seeder 182 cm, 3-Point Mounting, Non-CE	7167712	A770-B	-

Accessories For Loader-Compatible Attachments

Description	Item number	Compatible with attachment	Functional requirements
Bob-Tach Adapter	7167759	7167712 SEEDER 72SDR	-

BE OM **EN OFFERT**

Klicka bara på **knappen** eller skanna **QR-koden** nedan för åtkomst till vårt offertformulär.

Vi kontaktar dig så snart som möjligt. Tack!



BEGÄR OFFERT

